# Rainbow

| Technical            |                                                                                                                                                  |
|----------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| Country of Origin    | Australia                                                                                                                                        |
| Description          | Textured Loop Pile Carpet Tile                                                                                                                   |
| Yarn                 | 100% BCF Nylon                                                                                                                                   |
| Colours              | 20 Standard                                                                                                                                      |
| Tile Thickness       | 7.0 mm (tolerance ±1mm)                                                                                                                          |
| Pile Weight          | 746g/m² (22oz/yd²)                                                                                                                               |
| Gauge                | 47.2/10cm (1/12 <sup>th</sup> gauge)                                                                                                             |
| Backing Structure    | Enviro Bac® - Minimum of 60% recycled content                                                                                                    |
| Tile Size            | 500mm x 500mm                                                                                                                                    |
| Availability Options | Cut Pile Tile 1000mm x 500mm - Planks^ 1000mm x 250mm - Skinny Planks^ Enviro Bac Plus® - Cushion Backed Easy Grip™ - Adhesive Free Installation |
| Installation Method  | 1/4 Turn - Brick - Ashlar - Non Directional                                                                                                      |

| Performance                          |                                                                  |
|--------------------------------------|------------------------------------------------------------------|
| Anti-Static                          | AATCC 134 <3.5 Kilovolts at 21°C % 20% Relative Humidity         |
| Flammability<br>(AS ISO 9239.1.2003) | CRF 4.5kW/m <sup>2<sup>†</sup></sup><br>Smoke Value 518% Minutes |
| Colourfastness to Light              | 6-7 (Minimum mandatory performance for ACCS:5)                   |
| Light Reflectance Values             | Available Upon Request                                           |
| Stain Treatment                      | Stain Warden®                                                    |
| Biocontaminant Control               | Bioshield® Antimicrobial Treatment                               |
| ACCS Rating                          | Contract Extra Heavy & Duty & Stairs #12006 <sup>†</sup>         |
| Warranty                             | 15 Year*                                                         |

| Sustainability      |                                                                                                                                                                         |
|---------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| PVC Minimisation    | 100% PVC Free                                                                                                                                                           |
| Recycled Content    | Minimum of 60% recycled content in backing structure Minimum of 40% recycled content by weight of product                                                               |
| Indoor Air Quality  | Green Building Council & Green Label Plus compliant for VOC's emission rate limits <sup>†</sup>                                                                         |
| Product Stewardship | This product is RECYCLABLE and qualifies for take back at the end of life under the Godfrey Hirst Product Stewardship Program                                           |
| Green Star          | Environmental Certification Scheme (ECS) Level 4<br>Maximum points - Certification #12006 <sup>†</sup>                                                                  |
| Accreditation       | Manufactured under a quality, environmental and health and safety system certified and complying with ISO9001, ISO14001 and AS4801 by an accredited certification body. |

meets Green Label Plus specifications





## **HEAD OFFICE**

#### Geelong

7 Factories Rd, South Geelong, VIC 3220 Australia Fax +61 (0) 3 5222 3885

1300 444 778 general.enquiries@godfreyhirst.com www.godfreyhirst.com

## **SALES OFFICES**

#### Melbourne

2 Gilbertson Rd, Laverton North, VIC 3026

## **Sydney**

28 Percival Rd, Smithfield, NSW 2164

## **Brisbane**

33 Gassman Dr, Yatala, QLD 4207

#### Adelaide

8 Ware St, Thebarton, SA 5031

#### Perth

Unit 1 / 5 Leeway Crt Osborne Park, WA 6017

## INTERNATIONAL OFFICES

## **New Zealand**

FREECALL (NZ): 0800 500 210

## Auckland Office

142 Kerrs Rd, Wiri Manukau City, 2104 Auckland, New Zealand Ph +64 (0) 9 268 3300

## Wellington Office

C/- Canterbury Spinners 6 Bell Road South Lower Hutt, Wellington

## Christchurch Office

Unit 3, 9 Craft Place Middleton, Christchurch

## Singapore

200 Jalan Sultan #10/07 Textile Centre, Singapore, 199018.

Ph +65 6841 5529

Specifications and colourations are subject to nominal manufacturing tolerances. As part of Godfrey Hirst's continuous improvement program, Godfrey Hirst reserves the right to change specifications of of delete colours of this

All Godfrey Hirst carpet tile products must be installed in accordance with AS2455 (Parts 1&2) and the Godfrey Hirst Carpet Tile Installation Instructions

<sup>^</sup>Production time may vary depending on size of production run.

†Warranty terms and conditions apply.

<sup>†</sup>Test results and certificates are available or request.

