

## **Emission Test Certificate**

Tuesday 02<sup>nd</sup> April 2019

Supplier: Gerflor Australasia Pty Ltd (17 Cato St, Hawthorn East, VIC, 3123, Australia)

Sample Description: Gerflor Tarasafe Ultra H<sub>2</sub>O

Date Tested: March 2019 (Tested by FORAY Laboratories – NATA Accreditation 1231)

Test Method: ASTM D5116-2017 "Standard Guide for Small-Scale Environmental Chamber

Determinations of Organic Emissions from Indoor Material/Products".

Emission Data (24 hrs):

Green Building Council of Australia Green Star Design & As Built v1.1 - 13.1.2B & 13.2 Green Star Interiors V1.1 - 12.1.2B	Gerflor Tarasafe Ultra H₂O
Total Volatile Organic Compound Emission Rate Limit:	Total Volatile Organic Compound
≤0.500 mg/m²/hr	Emission Rate: 0.266 mg/m²/hr
Formaldehyde Emission Rate Limit:	Formaldehyde Emission Rate:
≤0.1 mg/m²/hr	0.013 mg/m²/hr

Dr. Vyt Garnys

PhD, BSc(Hons) AIMM, ARACI, ISIAQ

ACA, AIRAH, FMA

Managing Director and Principal Consultant

Nick Joy BSc(Hons)

Consultant

Tuan Duong

B.Eng. (Chemical)

Consultant

CV190328