SPORTS FLOORS



[1202] LOOSE LAYING TABLE TENNIS & BATECO

■ 1- TARAFLEX™ TABLE TENNIS

1.1 - Laying out the flooring

- The ambient temperature must be above 15 °C.
- Strike the transverse and longitudinal axis of the sports floor on the subfloor.


GERFLOR TABLE TENNIS is laid in the opposite direction from the table.

1.2 - Flattening

The roll must be ALLOWED TO LAY FLAT widthwise in the sports hall for at least 24 hours leaving a 1 cm overlap between each length and following the numbered order of the different lengths.

1.3 - Positionning


The roll are butted up to the axis and placed edge-to-edge without leaving a gap.



Double side tape adhesive under each roll and extremities

1.4 - Fixing the lengths

The lengths are held togetherwith double-sided adhesive tape D 200 on varnish wood from GERFLOR. The double-sidedadhesive tape is applied with a double side tape roller Ref. H372 0001 from Gerflor. **Note:** If it is being put down on a varnished wood strip flooring, check the adhesion proporties before installing. If the subfloor shows advertising logos or stuck-down game lines, they may be damaged.



IMPORTANT

GERFLOR cannot be liable for the performance of a double-sided adhesive tape which was not supplied by GERFLOR.

1.5 - Removal of the court

Remove the double-sided adhesive tape using the same machine as before.

- Roll the lengths on their packing tubes foam inside :
 - either manually
- or with a roll/unroll trolley
- Secure the sections with tightening straps
- Store the roll vertically or on suitable storing devices

■ 2 - REMOVABLE INSTALLATION OF THE BATECO PROTECTION FLOORING EXCLUDING SPORTING USAGE

Remark: Differences in width (tolerances) may exist between the strips.

2.1 - Unrolling

Unroll the strips by placing them side by side, as precisely as possible. There must not be any space between the strips.

The Bateco product has no shielding, it is thus mandatory to leave 40 cm excess on a 20 m strip and to let the product relax after 3 uses before adjusting the dimensions of the product to the room.

2.2 - Assembly

We recommend assembly with a single-side adhesive applied with the 50 or 100 mm wide single-face tape reel AT7 Ref. H2060001 from Gerflor



Single-side tape reel - H367 0003