

CARE AND PROTECTION

- This product has an acrylic PUR polyurethane treatment applied at time of manufacture, and as such is a low maintenance vinyl plank. This means there is no need to seal or polish when installed, unless there is a requirement for a higher gloss finish, or other aesthetic or hygiene considerations.
- Maintain the use of floor protector pads under the legs of furniture.
- **Rubber leaves indelible stains on vinyl flooring.** Avoid placing waxed or rubber products in prolonged contact with your Creation Clic floor.
- The use of mats in doorways will help protect the floor from scratches. **Do not use rubber mats** (including chair protection) over the Creation Clic floor.
- Avoid exposure to direct sunlight for prolonged periods. During peak sunlight hours use solar film, blinds or drapes to minimise direct sunlight and avoid discolouration.
- If Creation Clic has been loose laid in areas experiencing excessive heat, extreme temperature variations or direct sun, temperatures should be controlled between 15 and 28°C.
- If your Creation Clic floor is exposed to excessive water due to flooding, simply remove the water as quickly as possible by hand or mechanically and ensure the room is well ventilated.

INITIAL MAINTENANCE

- Remove loose dirt and debris from the newly installed floor using broom or vacuum.
- Ensure all adhesive residues are removed with due regard to supplier's recommendations. Do not use high abrasive pads or scourers.
- Wash floor with a neutral, pH7, detergent by low speed scrubbing machine fitted with nylon brushes or red pad (150-200 rpm). Ensure all detergent residues are rinsed and removed from the floor. In residential applications wash floor with a damp mop using a neutral pH7 floor cleaning detergent with water. Ensure all detergent residues are rinsed and removed from the floor.

GENERAL MAINTENANCE

- Remove loose dirt with broom or vacuum and damp mop regularly with neutral detergent.
- Prevent stains by wiping up spills immediately.

PERIODIC MAINTENANCE

- If available it is advised to machine auto scrub with nylon brush as required, or wash floor with a neutral detergent and buff with red pad at 450rpm.

REPAIRS

- Cut out the corner of the damaged plank and carefully remove. Take care not to damage surrounding planks.
- Select a spare plank and lift the new plank into place locking the edge pieces by gently manipulating the plank.
- Fine scratch marks as a result of household use can be eliminated through the application of two coats of a good quality vinyl floor finishing product.

If you have any queries about the care and maintenance of your Creation Clic floor, please contact Gerflor customer service.

