

PRODUCTS AFFECTED

Multi-Use	M Evolution	M Performance	M Comfort
Actionsport 50	M Plus	Performance Plus	Surface

GENERAL COMMENTS

Taraflex surfaces have a 100% PVC wear layer and a factory applied polyurethane protective treatment PROTECSOL[®], making it unnecessary to seal and polish the floor as part of a maintenance procedure, and classifying these products as low maintenance. A regular maintenance program is still essential to maximise the life span and appearance of the products.

INITIAL MAINTENANCE

Before commencing a regular maintenance program, it will be necessary to initially clean the floor to remove dirt etc. accumulated from installation and other building procedures.

- Remove loose dirt and debris from the newly installed floor using broom or vacuum
- Wash floor with damp mop and bucket containing warm water and neutral detergent, replacing solution as necessary.
- If necessary, use a low speed scrubbing machine fitted with nylon brushes or red pad.

DAILY MAINTENANCE

Cleaning frequency of will depend on traffic; this procedure has been drawn up with the use of a multipurpose hall in mind.

- Remove loose dirt with broom or vacuum; damp mop with neutral detergent.
- Wash floor with a neutral detergent by low speed scrubbing machine fitted with nylon brushes or red pad. Gerflor recommends Rotowash.
- Spot cleaning as required to remove scuff marks. Gerflor recommends Elatex Stain Doctor.

PRECAUTION

- DO NOT polish the Taraflex Sports floor
- No black soled shoes on the floor
- Walk off mats from entries

For further enquiries regarding the maintenance of Gerflor products, please contact your Gerflor Technical Manager.

