

**DESCRIPTION**

Total thickness	EN 428	mm	5.00
Weight	EN 430	g/m <sup>2</sup>	7420
Tile size	EN 427	mm	635 x 635


**CLASSIFICATION**

Norm / Product specification	-	-	EN 649
European classification	EN 685	class	34 - 43
Fire rating / Critical flux	EN ISO 9239-1	kW/m <sup>2</sup>	7.62
Fire rating / Smoke density	EN ISO 9239-1	% min	531
Static electrical propensity	EN 1815	kV	< 2
Slip resistance wet: ramp test with oil	DIN 51130	class	R10

**PERFORMANCE**

Wear resistance	EN 660.2	mm <sup>3</sup>	≤ 2.0
Wear Group	EN 649	group	T
Type Binder content	ISO 10582	type	I
Dimensional stability	EN 434	%	≤ 0.25
Residual indentation	EN 433	mm	≤ 0.10
Impact sound insulation	EN ISO 717-2	dB	4
Castor chair test (type W)	EN 425	-	OK
Thermal conductivity	EN 12 524	W/(m.K)	0.25
Colour fastness	EN 20 105 - B02	degree	≥ 6
Chemical products resistance	EN 423	class	OK
Anti-bacterial and fungicidal treatment	EN ISO 846	-	Sanosol®
Surface treatment	-	-	PUR+
TVOC after 28 days	ISO 16000-6	µg/ m <sup>3</sup>	< 100

**CE MARKING**

	EN 14041	-	
--	----------	---	---

CE

